




## PATTA-I

**LED outdoor recessed ceiling light, angular DL IP65 silver 1800-3000K**

The innovative PATTA-I recessed light is suitable for ceiling thicknesses up to 20 mm. Thanks to its IP65 rating, it is suitable for use outdoors and in wet rooms. The light is available in black, white or silver grey, and in a round or square shape. It is fitted with a powerful, dim-to-warm LED, which allows the light colour to be individually adjusted. Thanks to the integrated LED driver, the light can be connected directly to the 230 V mains voltage.



## TECHNICAL DATA

|                            |  |
|----------------------------|--|
| Item no.                   | 1002103                                  |
| IP Code                    | IP 20 / IP 65                            |
| Impact resistance class    | IK 02                                    |
| Impact resistance          | 0.2 Joule                                |
| Assembly                   | Recessed                                 |
| Assembly details           | Ceiling                                  |
| Dimmable                   | Yes                                      |
| Dimming technology         | Dim-to-Warm, Leading edge, trailing edge |
| Primary nominal voltage    | 220-240V ~50/60Hz                        |
| Secondary power / voltage  | 350 mA                                   |
| Safety class               | II                                       |
| Wattage                    | 7.3 W                                    |
| Level of inrush current    | 2 A                                      |
| Duration of inrush current | 40 $\mu$ s                               |
| Stroboscopic effect (SVM)  | 0.02                                     |
| Lumen                      | 440 lm                                   |
| Colour temperature         | 1800-3000 Kelvin                         |
| Beam angle                 | 38 °                                     |
| Color                      | aluminium                                |
| CRI                        | 95                                       |
| LXXBXX data                | L70B50                                   |
| Service life               | 30000 h                                  |



## Light Source

916436 

|                       |          |
|-----------------------|----------|
| Length                | 8 cm     |
| Width                 | 8 cm     |
| Height                | 4 cm     |
| Net weight            | 0.236 kg |
| Gross weight          | 0.288 kg |
| Shape of cut-out      | round    |
| Installation depth    | 6 cm     |
| Installation diameter | 6 cm     |

