




## HELIA 40 PD

**LED indoor pendant, soft gold, 3000K, surface-mounted version**

With the HELIA 40 you have a pendant with a purist and clear design. This luminaire is available in soft gold, black, white and brushed copper. A 9 W warm-white premium LED is integrated, this is supplied from the built-in constant current driver. The luminaire is delivered with a 1.5 m connection lead. This means the luminaire is ready for direct connection to the 230V mains supply.



## TECHNICAL DATA

Item no.	1002171
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	10 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	10 A
Duration of inrush current	40 µs
Stroboscopic effect (SVM)	0.02
Lumen	790 lm
Colour temperature	3000 Kelvin
Beam angle	30 °
Color	gold
CRI	90
LXXBXX data	L70B50
Service life	30000 h



## Light Source

916387	
--------	---

Length	45 cm
Diameter	4 cm
Pendant length	150 cm
Net weight	0.905 kg
Gross weight	1.104 kg

