



## LED SPIKE

**LED outdoor ground spike luminaire, rust coloured, IP55, 3000K, 40°**

The LED SPIKE ground spike luminaire is available in several colour variants and comes equipped with a powerful, warm-white 6 Watt LED. The luminaire is made of aluminium and is connected using the supply cable incl. plug directly to the 230V mains supply. Thanks to its IP55 protection class, the luminaire is suitable for outdoor use.

## TECHNICAL DATA

|                             |                   |
|-----------------------------|-------------------|
| Item no.                    | 1002203           |
| IP Code                     | IP 55             |
| Impact resistance class     | IK 06             |
| Impact resistance           | 1 Joule           |
| Assembly                    | Mobile            |
| Primary nominal voltage     | 100-240V ~50/60Hz |
| Secondary power / voltage   | 240 mA            |
| Safety class                | I                 |
| Wattage                     | 6 W               |
| Minimum ambient temperature | -20 °C            |
| Maximum ambient temperature | 45 °C             |
| Level of inrush current     | 1.12 A            |
| Stroboscopic effect (SVM)   | 1.66              |
| Lumen                       | 400 lm            |
| Colour temperature          | 3000 Kelvin       |
| Beam angle                  | 40 °              |
| Color                       | rust              |
| CRI                         | 80                |
| LXXBXX data                 | L70B50            |
| Service life                | 30000 h           |
| Length                      | 8 cm              |
| Height                      | 10 cm             |



## Light Source

916630 

|                       |          |
|-----------------------|----------|
| Diameter              | 6 cm     |
| Length of earth spike | 17.2 cm  |
| Net weight            | 0.588 kg |
| Gross weight          | 0.659 kg |
| BIG WHITE Page        | 701      |