




VILUA S WL

**Outdoor recessed wall light, anthracite, 3000K IP54
100° 405lm**

The VILUA wall light, which is equipped with powerful, warm white LEDs, is available in several versions. The electrical connection of the luminaire, which is made from aluminium, is made directly to the 230V mains supply. Thanks to its IP54 protection class, the luminaire is suitable for outdoor use. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.	1002503
IP Code	IP 54
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Wall
Primary nominal voltage	100-277V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	9 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	73.2 A
Duration of inrush current	1.4 µs
Stroboscopic effect (SVM)	0.02
Lumen	405 lm
Colour temperature	3000 Kelvin
Beam angle	100 °
Color	anthracite
CRI	80
LXXBXX data	L70B50
Service life	30000 h



Light Source

916530 

Width	12 cm
Height	12 cm
Depth	5.8 cm
Net weight	0.585 kg
Gross weight	0.709 kg
BIG WHITE Page	763

