




## VILUA L WL

**Outdoor recessed wall light, anthracite, 3000K IP54  
100° 810lm**

The VILUA wall light, which is equipped with powerful, warm white LEDs, is available in several versions. The electrical connection of the luminaire, which is made from aluminium, is made directly to the 230V mains supply. Thanks to its IP54 protection class, the luminaire is suitable for outdoor use. This luminaire contains built-in LED lamps.



## TECHNICAL DATA

Item no.	1002504
IP Code	IP 54
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Wall
Primary nominal voltage	100-277V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	17 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Level of inrush current	17 A
Duration of inrush current	35 µs
Stroboscopic effect (SVM)	0.02
Lumen	940 lm
Colour temperature	3000 Kelvin
Beam angle	100 °
Color	anthracite
CRI	80
LXXBXX data	L70B50
Service life	30000 h



## Light Source

916374 

Width	20 cm
Height	20 cm
Depth	9 cm
Net weight	1.603 kg
Gross weight	1.933 kg
BIG WHITE Page	763

