




DOWNUNDER OUT

round WL Outdoor LED recessed wall light, anthracite, 3000K

A wall-mounted light such as the DOWNUNDER OUT is protected against water jets from all directions and also against dust deposits. Protection category IP55 guarantees problem-free use outdoors. Here at SLV, we work hard on our service and our lights, to ensure that you are satisfied. This attitude and our commitment to quality and design have allowed us to enjoy success for almost 40 years. For this reason, we offer a 5-year warranty for our products.



TECHNICAL DATA

Item no.	1002868
IP Code	IP 65
Assembly	Surface
Assembly details	Wall
Primary nominal voltage	100-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	4.3 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	15 A
Duration of inrush current	300 µs
Stroboscopic effect (SVM)	0
Lumen	150/160 lm
Colour temperature	3000/4000 Kelvin
Color	anthracite
CRI	80
LXXBXX data	L70B50
Service life	30000 h
Risk Group	1
Depth	4.4 cm
Diameter	14 cm



Light Source

916443	
--------	---

Net weight	0.412 kg
Gross weight	0.495 kg
BIG WHITE Page	769