


LIPSY 50 DRUM DALI CW

LED Indoor surface-mounted wall and ceiling light, white, 3000/4000 K

Because of their timeless and discreet design, the wall and ceiling lights in the LIPSY DRUM DALI series are a popular lighting solution for a wide range of applications. The steel and acrylic glass luminaires come in a variety of housing sizes. The wide beam characteristic creates homogeneous lighting in combination with the powerful LED module. The built-in DALI-compatible LED driver makes it possible to connect directly to a 230V mains power supply. The light colour of the product can be switched between 3000 K and 4000 K.



TECHNICAL DATA

Item no.	1002941
IP Code	IP44
Impact resistance class	IK 02
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	21 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	15 A
Duration of inrush current	500 µs
Lumen	2450/2600 lm
Colour temperature	3000/4000 Kelvin
Beam angle	120 °
Color	white
CRI	80
Service life	30000 h
Risk Group	0
Height	9.6 cm
Diameter	40 cm

Light Source

916360	

Net weight	1.047 kg
Gross weight	1.569 kg
BIG WHITE Page	468