




## NOBLO III

Indoor LED surface-mounted ceiling light 2700K white

NOBLO rotating and tilting LED spotlight for surface mounting on walls and ceilings. The luminaire impresses with its slim design and is therefore ideal for modern lighting concepts. The luminaire is made from aluminium and equipped with a Premium LED module. The luminaire is available in three housing colours with two or three light outlets.



## TECHNICAL DATA

|                                   |                         |
|-----------------------------------|-------------------------|
| Item no.                          | 1002977                 |
| Number of different light outlets | 3                       |
| Rotating or tilting               | rotary Bar and tiltable |
| IP Code                           | IP 20                   |
| Assembly                          | Surface                 |
| Assembly details                  | Ceiling, Wall           |
| Dimmable                          | Yes                     |
| Dimming technology                | trailing edge           |
| Primary nominal voltage           | 220-240V ~50/60Hz       |
| Secondary power / voltage         | 350 mA                  |
| Safety class                      | I                       |
| Wattage                           | 24 W                    |
| Minimum ambient temperature       | -20 °C                  |
| Maximum ambient temperature       | 30 °C                   |
| Operating efficiency (LOR)        | 0,8                     |
| Number of luminaires at LS B16A   | 128                     |
| Number of luminaires at LS C16A   | 160                     |
| Level of inrush current           | 3.5 A                   |
| Duration of inrush current        | 120 µs                  |
| Stroboscopic effect (SVM)         | 0.4                     |
| Lumen                             | 1860 lm                 |
| Colour temperature                | 2700 Kelvin             |



## Light Source

|        |   |
|--------|---|
| 916369 |  |
|--------|---|

|                |          |
|----------------|----------|
| Beam angle     | 36 °     |
| Color          | white    |
| CRI            | 80       |
| LXXBXX data    | L70B50   |
| Service life   | 30000 h  |
| Risk Group     | 1        |
| Length         | 40 cm    |
| Width          | 10.5 cm  |
| Height         | 12.7 cm  |
| Net weight     | 1.012 kg |
| Gross weight   | 1.347 kg |
| BIG WHITE Page | 401      |

