



NOTAPO II

Indoor recessed wall light 3000K white

Aluminium recessed wall light NOTAPO II WL. The invisibly installed LED emits its light indirectly onto the surface to be illuminated. This makes glare-free illumination of walkways and staircases possible, for example. The NOTAPO II recessed fitting is available with a white housing. An installation frame and a mounting box for installation in masonry are optionally available. This luminaire contains built-in LED lamps.

TECHNICAL DATA

Item no.	1002980
IP Code	IP 20
Assembly	Recessed
Assembly details	Wall, Wall with Acc.
Secondary power / voltage	700 mA
Safety class	III
Wattage	2.2 W
Maximum ambient temperature	40 °C
Lumen	6 lm
Colour temperature	3000 Kelvin
Color	white
CRI	90
LXXBXX data	L70B50
Service life	35000 h
Light distribution	asymmetric
Light outlet	indirect
Width	3.6 cm
Height	18 cm
Depth	3.8 cm
Net weight	0.104 kg
Gross weight	0.157 kg
Shape of cut-out	square



Light Source

954799	
--------	---

Accessories

1007213	LED DRIVER , 10W, 700-mA, PHASE, incl. strain relief
1007216	LED driver 3W , 700mA incl. strain relief
1007229	LED driver 25W 150-700-mA DALI TOUCH
1002981	NOTAPO I and II WL , installation frame

Installation length	17.3 cm
Installation width	2.8 cm
Installation depth	5 cm
BIG WHITE Page	241

