




ABRIDOR SENSOR

Outdoor LED surface-mounted wall light IP55 anthracite 3000/4000K

The aluminium luminaires in the ABRIDOR family provide solutions for the wall light and floor stand area. Thanks to its IP55 protection class, the luminaires are suitable for outdoor use. The electrical connection is made directly to the 230V mains power supply. The unusual lamp head means that the built-in LED has particularly wide light distribution.




TECHNICAL DATA

| | |
|-----------------------------|-------------------|
| Item no. | 1002990 |
| Rotating or tilting | tiltable |
| IP Code | IP 54 |
| Impact resistance class | IK 03 |
| Impact resistance | 0.35 Joule |
| Assembly | Surface |
| Assembly details | Wall |
| Primary nominal voltage | 100-240V ~50/60Hz |
| Secondary power / voltage | 300 mA |
| Safety class | I |
| Wattage | 12 W |
| Minimum ambient temperature | -25 °C |
| Maximum ambient temperature | 40 °C |
| Level of inrush current | 5 A |
| Duration of inrush current | 100 µs |
| Stroboscopic effect (SVM) | 0.02 |
| Lumen | 950/980 lm |
| Colour temperature | 3000/4000 Kelvin |
| Beam angle | 100 ° |
| Color | anthracite |
| CRI | 80 |
| LXXBXX data | L70B50 |



Light Source

| | |
|--|---|
| |  |
|--|---|

| | |
|----------------|----------|
| Service life | 30000 h |
| Length | 14 cm |
| Height | 16 cm |
| Depth | 17.5 cm |
| Net weight | 1.272 kg |
| Gross weight | 1.545 kg |
| BIG WHITE Page | 770 |