



## SENSER 12

Indoor LED surface-mounted ceiling light round white 3000K


The flat SENSER wall and ceiling light made from aluminium is available in white and silver-grey, in a round or square version. The rigid Premium LED insert produces homogeneous base illumination over a wide area thanks to its extensive beam angle.

### TECHNICAL DATA

Item no.	1003014
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ceiling, Wall
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	200 mA
Safety class	I
Wattage	8.4 W
Ambient temperature	25 °C
Operating efficiency (LOR)	0,56
Number of luminaires at LS B16A	92
Number of luminaires at LS C16A	92
Level of inrush current	3.4 A
Duration of inrush current	40 µs
Stroboscopic effect (SVM)	0.08
Lumen	460 lm
Colour temperature	3000 Kelvin
Color	white



## Light Source

1100375 

CRI	90
UGR $\leq$	30
LXXBXX data	L70B50
Service life	48000 h
Risk Group	1
Height	3.5 cm
Diameter	11.5 cm
Net weight	0.271 kg
Gross weight	0.316 kg
BIG WHITE Page	419

