




DINGILO

Indoor LED recessed ceiling light black 2700K tiltable

This should be your choice of recessed ceiling light if colour rendering is very important to you. With a CRI value of over 90, the DINGILO is extremely suitable for true-colour lighting of rooms.



TECHNICAL DATA

Item no.	1003036
Rotating or tilting	tiltable
IP Code	IP 20 / IP 44
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Primary nominal voltage	100-277V ~50/60Hz
Secondary power / voltage	200 mA
Safety class	II
Wattage	4.4 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	13 A
Duration of inrush current	300 µs
Stroboscopic effect (SVM)	0
Lumen	330 lm
Colour temperature	2700 Kelvin
Beam angle	40 °
Color	black
CRI	90
LXXBXX data	L70B50



Light Source

916578	
--------	---

Service life	30000 h
Light distribution	rotational symmetric
Light outlet	direct
Height	4 cm
Diameter	8 cm
Net weight	0.213 kg
Gross weight	0.275 kg
Installation depth	4 cm
Installation diameter	6.8 cm

