




I-PENDANT PRO DALI

Indoor LED pendant UGR<19 white 4000K

With the I-PENDANT PRO DALI, which is available with several different light colours, we are providing a modern and space-saving solution for an efficient kind of basic lighting with the additional possibility of DALI control. The high degree of luminous flux provides a pleasant, homogeneous and glare-free lighting sensation. The electrical connection is made via the built-in LED power supply directly to a 100-240V mains power supply.



TECHNICAL DATA

| | |
|-----------------------------|-------------------|
| Item no. | 1003049 |
| IP Code | IP 20 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | DALI |
| Primary nominal voltage | 120-277V ~50/60Hz |
| Secondary power / voltage | 1000 mA |
| Safety class | II |
| Wattage | 43 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Network rated standby power | 0.3 W |
| Level of inrush current | 30 A |
| Duration of inrush current | 30 µs |
| Stroboscopic effect (SVM) | 0.02 |
| Lumen | 3800 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 90 ° |
| Color | white |
| CRI | 80 |
| UGR ≤ | 19 |



Light Source

| | |
|--------|--|
| 916310 | |
|--------|--|

| | |
|----------------|----------|
| LXXBXX data | L70B50 |
| Service life | 30000 h |
| Length | 119.5 cm |
| Width | 29.5 cm |
| Height | 1.3 cm |
| Pendant length | 170 cm |
| Net weight | 5.1 kg |
| Gross weight | 6.263 kg |
| BIG WHITE Page | 289 |

