




## PANEL DALI

Indoor LED surface-mounted ceiling lights  
1200x300mm white 3000K

The PANEL DALI pendant, which is available in several different light colours, impresses with its ultra-flat design and powerful, dimmable LED modules. The aluminium frame is fitted with an acrylic glass cover which provides homogeneous and glare-free illumination. The built-in DALI-compatible operating device makes direct connection to a mains power supply of 100V - 240V possible.



## TECHNICAL DATA

Item no.	1003052
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	120-277V ~50/60Hz
Secondary power / voltage	1000 mA
Safety class	I
Wattage	43 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Network rated standby power	0.3 W
Level of inrush current	30 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0.02
Lumen	3100 lm
Colour temperature	3000 Kelvin
Beam angle	90 °
Color	white
CRI	80
UGR ≤	19



## Light Source

916537	
--------	---

LXXBXX data	L70B50
Service life	30000 h
Length	119.5 cm
Width	29.5 cm
Height	5 cm
Net weight	4.459 kg
Gross weight	5.33 kg
BIG WHITE Page	275

