




## NEW TRIA 68 I CS

Indoor LED recessed ceiling light black round 3000K  
38° incl. driver clip springs

Are you looking for amazing light for your rooms? You get this thanks to the integrated Premium LED in the NEW TRIA 68 I CS recessed ceiling light. With a CRI value of equal to or greater than 80, the recessed ceiling light NEW TRIA 68 I CS is particularly suitable for illuminating of sales or office premises.



## TECHNICAL DATA

Item no.	1003057
Rotating or tilting	tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Primary nominal voltage	100-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	II
Wattage	4 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	10 A
Duration of inrush current	92 µs
Stroboscopic effect (SVM)	0.01
Lumen	360 lm
Colour temperature	3000 Kelvin
Beam angle	38 °
Color	black
CRI	80
LXXBXX data	L70B50
Service life	40000 h
Risk Group	0



## Light Source

916559	
--------	---

Height	3.5 cm
Diameter	8.2 cm
Net weight	0.199 kg
Gross weight	0.247 kg
Shape of cut-out	round
Installation depth	3.5 cm
Installation diameter	6.8 cm

