




## NEW TRIA 68 I CS

Indoor LED recessed ceiling light alu round 2700K 38° incl. driver clip springs

The premium LED integrated in the NEW TRIA 68 I CS recessed ceiling light gives off a particularly warm light. With a CRI value of greater than or equal to 80, the NEW TRIA 68 I CS is very suitable for true-colour lighting of office or sales premises. This recessed ceiling light is sustainable and low-maintenance thanks to the anticipated service life of 40,000 hours.



## TECHNICAL DATA

Item no.	1003060
Rotating or tilting	tiltable
Assembly	Recessed
Assembly details	Ceiling
Primary nominal voltage	100-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	II
Wattage	4 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	10 A
Duration of inrush current	92 µs
Stroboscopic effect (SVM)	0.01
Lumen	330 lm
Colour temperature	2700 Kelvin
Beam angle	38 °
Color	aluminium
CRI	80
LXXBXX data	L70B50
Service life	40000 h
Risk Group	0
Height	3.5 cm



## Light Source

916479	
--------	---

Diameter	8.2 cm
Net weight	0.196 kg
Gross weight	0.239 kg
Shape of cut-out	round
Installation depth	3.5 cm
Installation diameter	6.8 cm

