




## LED PANEL 620x620

Indoor LED recessed ceiling light white 4000K  
UGR<19

The LED PANEL for grid ceilings, which can be switched between two light colours, is a modern and space saving solution for an efficient kind of basic lighting. You achieve a pleasant, homogeneous and glare-free lighting sensation with this product, with an aperture angle of less than 19°.



## TECHNICAL DATA

Item no.	1003074
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling,Ceiling with Acc.
Secondary power / voltage	1050 mA
Safety class	III
Wattage	35 W
Lumen	4000 lm
Colour temperature	4000 Kelvin
Beam angle	120 °
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L70B50
Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Length	61.7 cm
Width	61.7 cm
Height	0.9 cm
Net weight	3.151 kg

## Light Source

916349	
--------	---

## Accessories

1006197	LED driver , 40W 1050-mA DALI dimmable with RF interface LED driver white DALI
158791	CEILING PLATE , for LED PANEL, I-VIDUAL and I-VIDUAL LED PANEL, white
1006454	RF module Casambi for LED bridge driver , single colour
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1002425	LED driver MEDO 600 , dimmable DALI/1-10V
464804	LED DRIVER , 40W, 1050mA, triac dimmable
158799	SUSPENSION SET , for LED PANEL, I-VIDUAL and I-VIDUAL LED PANEL, steel wire and Y-wire suspension

Gross weight	3.769 kg
Shape of cut-out	square
Installation depth	5 cm
BIG WHITE Page	243