




## ENOLA ROUND UP/- DOWN M

outdoor LED surface-mounted wall light anthracite

The ENOLA SQUARE and ROUND light series have a purist style, consisting of a cylindrical or square aluminium construction fitted with powerful LEDs. Thanks to the integrated CCT switch, the light colour can be altered between 3000 K and 4000 K on installation. Thanks to the integrated LED driver, the electrical connection for the light is made directly to the 230 V mains voltage. In order to cover as wide a range of applications as possible, you can opt for one or two-lamp wall lights or ceiling lights in round or square form and in different sizes. This light contains integrated LED light bulbs.



### TECHNICAL DATA

Item no.	1003425
Number of different light outlets	2
IP Code	IP65
Impact resistance class	IK 06
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Wall, Wall with Acc.
Number of through-wires	37
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	37
Number of luminaires at LS C16A	74
Level of inrush current	10 A
Duration of inrush current	300 µs
Stroboscopic effect (SVM)	0.07
Lumen	1660/1900 lm
Colour temperature	3000/4000 Kelvin
Beam angle	38 °

## Light Source

916566	
--------	---

## Accessories

1002853	Spacer set , for outdoor wall-mounted lights anthracite
1005206	ENOLA M , lens asymmetric
1005205	ENOLA M , lens 20°
1005207	ENOLA M , reflector 60°

CRI	90
LXXBXX data	L70B50
Service life	30000 h
Risk Group	1
Width	10 cm
Height	23 cm
Depth	15 cm
Net weight	1.671 kg
Gross weight	2.005 kg
BIG WHITE Page	727