




QUAD FRAME 19

indoor LED surface-mounted wall light TRIAC white
CCT switch 2700/3000K

LED surface-mounted wall light QUAD FRAME 14. The invisibly installed LED emits its light indirectly onto the surface to be illuminated. This makes glare-free illumination of walkways and staircases possible, for example. The QUAD FRAME 14 recessed fitting is available in white colour version. The light colour can be switched between 2700K and 3000K during installation using the built-in CCT switch. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.	1003468
IP Code	IP20
Assembly	Surface
Assembly details	Wall
Number of through-wires	10
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	11 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	4.7 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0.02
Lumen	580/640 lm
Colour temperature	2700/3000 Kelvin
Beam angle	100 °
Color	white
CRI	90
LXXBXX data	L70B50
Service life	30000 h
Risk Group	0



Light Source

916552 

Width	18.5 cm
Height	15.5 cm
Depth	5.2 cm
Net weight	0.678 kg
Gross weight	0.841 kg
BIG WHITE Page	364

