






OUT-BEAM FRAME CW

Outdoor LED wall and ceiling mounted light anthracite 3000K

With the anthracite-coloured OUT-BEAM FRAME CW, you have an outdoor surface-mounted light which is ideally suited for accentuating buildings. This light is intended for use in both residential and public areas. Thanks to the OU-T-BEAM FRAME CW you can illuminate historical or modern buildings with wonderful effects. With an expected lifespan of 30,000 hours, the LED light is extremely sustainable and requires little maintenance.



TECHNICAL DATA

Item no.	1003518
IP Code	IP 55
Impact resistance class	IK 03
Impact resistance	0.35 Joule
Assembly	Surface
Assembly details	Ceiling, Ground, Wall
Number of through-wires	10
Primary nominal voltage	100-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	3.5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	15 A
Duration of inrush current	300 μs
Stroboscopic effect (SVM)	0
Lumen	60 lm
Colour temperature	3000 Kelvin
Beam angle	5°
Color	anthracite
CRI	80
LXXBXX data	L70B50





Light Source

Å G 916607

Service life	30000 h
Risk Group	1
Length	17.3 cm
Width	8.5 cm
Height	6.7 cm
Net weight	0.61 kg
Gross weight	0.653 kg
BIG WHITE Page	811