




OUT-BEAM FRAME CW

Outdoor LED wall and ceiling mounted light white 3000K

With the white OUT-BEAM FRAME CW, you have an outdoor surface-mounted light which is ideally suited for accentuating buildings. This light is intended for use in both residential and public areas. Thanks to the OUT-BEAM FRAME CW you can illuminate historical or modern buildings with wonderful effects. With an expected lifespan of 30,000 hours, the LED light is extremely sustainable and requires little maintenance.



TECHNICAL DATA

Item no.	1003519
IP Code	IP 55
Impact resistance class	IK 03
Impact resistance	0.35 Joule
Assembly	Surface
Assembly details	Ceiling,Ground,Wall
Number of through-wires	10
Primary nominal voltage	100-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	3.5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	15 A
Duration of inrush current	300 µs
Stroboscopic effect (SVM)	0
Lumen	60 lm
Colour temperature	3000 Kelvin
Beam angle	5 °
Color	white
CRI	80
LXXBXX data	L70B50



Light Source

916607	
--------	---

Service life	30000 h
Risk Group	1
Length	17.3 cm
Width	8.5 cm
Height	6.7 cm
Net weight	0.657 kg
Gross weight	0.781 kg
BIG WHITE Page	811

