




L-LINE OUT 80 FL POLE

Outdoor LED free-standing light horizontal anthracite
CCT switch 3000/4000K

Whether in gardens, along the paths and driveways of residential buildings, hotels or restaurants - with its variety of lights, the L-LINE OUT family lights the way outdoors. Despite their individual differences, the individual members share a design vocabulary in L-shape, which stands out with its clear lines. And when it comes to lighting technology, there are no compromises: the choice of light colour (3000/4000K), which can be selected during the easy installation process, and IP protection class 65 are just some of the benefits of the L-LINE OUT.



TECHNICAL DATA

| | |
|-----------------------------------|-------------------|
| Item no. | 1003538 |
| Number of different light outlets | 1 |
| IP Code | IP 65 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly | Surface |
| Assembly details | Ground |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 350 mA |
| Safety class | I |
| Wattage | 7 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 45 °C |
| Level of inrush current | 10 A |
| Duration of inrush current | 40 µs |
| Stroboscopic effect (SVM) | 0.08 |
| Lumen | 490/530 lm |
| Colour temperature | 3000/4000 Kelvin |
| Color | anthracite |
| CRI | 80 |
| LXXBXX data | L70B50 |
| Service life | 30000 h |



Light Source

| | |
|--------|---|
| 916406 |  |
|--------|---|

Accessories

| | |
|--------|---------------------------------|
| 228730 | CONNECTION BOX , 3-pin, IP68 |
|--------|---------------------------------|

| | |
|----------------|----------|
| Light outlet | direct |
| Risk Group | 0 |
| Length | 15 cm |
| Width | 10 cm |
| Height | 80 cm |
| Net weight | 2.672 kg |
| Gross weight | 3.358 kg |
| BIG WHITE Page | 651 |

