



## NUMINOS® MOVE DL M

**Indoor LED recessed ceiling light black/white 3000K  
55° rotating and pivoting**

The NUMINOS light system from SLV perfectly combines function, design and technology. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Like with the NUMINOS® MOVE DL M recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light has a power consumption of 17.55 watts, a luminous flux of 1600 lumens, a colour temperature of 3000 Kelvin and a good colour reproduction index of over 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

## TECHNICAL DATA

Item no.	1003584
Number of different light outlets	1
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	500 mA
Safety class	III
Wattage	17.55 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	1600 lm
Colour temperature	3000 Kelvin
Beam angle	55 °
Color	black
CRI	90
UGR ≤	22
LXXBXX data	L80B50
Service life	50000 h
Light distribution	rotational symmetric

## Light Source

791822	
--------	---

## Accessories

1004792	NUMINOS® M , diffuser Frosted
1004069	LED driver , 29W 500mA
1004064	LED driver , 21-29.5W 500/600/700mA
1006459	LED bridge driver , 42W, 500mA for NUMINOS®, including radio interface for RF module, DALI
1006143	Numinos® M Reducing ring , round 240/120mm black
1004054	LED driver , 20W 500mA PHASE
1006146	Numinos® M Reducing ring , square 240/120mm white
1006454	RF module Casambi for LED bridge driver , single colour
1006144	Numinos® M Reducing ring , round 240/120mm white
1004793	NUMINOS® M , diffuser Wabe
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1006145	Numinos® M Reducing ring , square 240/120mm black
1004790	NUMINOS® M , diffuser Ellipse
1004791	NUMINOS® M , diffuser Prisma

Light outlet	direct
Risk Group	1
Height	9 cm
Diameter	13.5 cm
Net weight	0.39 kg
Gross weight	0.45 kg
Shape of cut-out	round
Installation depth	10 cm
Installation diameter	12 cm
<b>BIG WHITE Page</b>	87