



NUMINOS® MOVE DL M

**Indoor LED recessed ceiling light white/white 4000K
40° rotating and pivoting**

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With a variety of downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® MOVE DL M recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light has a power consumption of 17.55 watts, a luminous flux of 1750 lumens, a colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When will you choose SLV's modular variety?

TECHNICAL DATA

Item no.	1003617
Number of different light outlets	1
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	500 mA
Safety class	III
Wattage	17.55 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	1750 lm
Colour temperature	4000 Kelvin
Beam angle	40 °
Color	white
CRI	90
UGR ≤	22
LXXBXX data	L80B50
Service life	50000 h
Light distribution	rotational symmetric

Light Source

791825	
--------	---

Accessories

1004792	NUMINOS® M , diffuser Frosted
1004069	LED driver , 29W 500mA
1004064	LED driver , 21-29.5W 500/600/700mA
1006459	LED bridge driver , 42W, 500mA for NUMINOS®, including radio interface for RF module, DALI
1006143	Numinos® M Reducing ring , round 240/120mm black
1004054	LED driver , 20W 500mA PHASE
1006146	Numinos® M Reducing ring , square 240/120mm white
1006454	RF module Casambi for LED bridge driver , single colour
1006144	Numinos® M Reducing ring , round 240/120mm white
1004793	NUMINOS® M , diffuser Wabe
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1006145	Numinos® M Reducing ring , square 240/120mm black
1004790	NUMINOS® M , diffuser Ellipse
1004791	NUMINOS® M , diffuser Prisma

Light outlet	direct
Risk Group	1
Height	9 cm
Diameter	13.5 cm
Net weight	0.39 kg
Gross weight	0.45 kg
Shape of cut-out	round
Installation depth	10 cm
Installation diameter	12 cm
BIG WHITE Page	87