



NUMINOS® MOVE DL L

**Indoor LED recessed ceiling light black/chrome 2700K
55° rotating and pivoting**

The NUMINOS light system from SLV combines technology, design and functionality like no other. The diverse downlights and spotlights make a thousand lighting design options possible. This also includes NUMINOS® MOVE DL L, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light convinces with a power consumption of 25.41 watts, luminous flux of 2150 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.

TECHNICAL DATA

| | |
|-----------------------------------|-------------------------|
| Item no. | 1003633 |
| Number of different light outlets | 1 |
| Rotating or tilting | rotary Bar and tiltable |
| IP Code | IP 20 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Secondary power / voltage | 700 mA |
| Safety class | III |
| Wattage | 25.41 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Lumen | 2150 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 55 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 19 |
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Light distribution | rotational symmetric |

Light Source

| | |
|--------|---|
| 791800 |  |
|--------|---|

Accessories

| | |
|---------|--|
| 1006148 | Numinos® L Reducing ring , round 240/150mm white |
| 1006149 | Numinos® L Reducing ring , square 240/150mm black |
| 1004062 | LED driver , 21-29.5W 500/600/700mA for Numinos Downlight Serie |
| 1004795 | NUMINOS® L , diffuser Prisma |
| 1004796 | NUMINOS® L , diffuser Frosted |
| 1006460 | LED bridge driver , 42W, 700mA for NUMINOS®, including radio interface for RF module, DALI |
| 1004794 | NUMINOS® L , diffuser Ellipse |
| 1006150 | Numinos® L Reducing ring , square 240/150mm white |
| 1006454 | RF module Casambi for LED bridge driver , single colour |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour |
| 1006147 | Numinos® L Reducing ring , round 240/150mm black |
| 1004070 | LED driver , 40W 700mA DALI |
| 1004797 | NUMINOS® L , diffuser Wabe |
| 1004065 | LED driver , 30W 700mA |

| | |
|-----------------------|---------|
| Light outlet | direct |
| Risk Group | 1 |
| Height | 9.5 cm |
| Diameter | 16 cm |
| Net weight | 0.54 kg |
| Gross weight | 0.68 kg |
| Shape of cut-out | round |
| Installation depth | 10.5 cm |
| Installation diameter | 14.5 cm |
| BIG WHITE Page | 87 |