



## NUMINOS® MOVE DL XL

**Indoor LED recessed ceiling light black/black 2700K  
40° rotating and pivoting**

The NUMINOS light system from SLV combines technology, design and functionality like no other. With various downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® MOVE DL XL recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light can convince with a power consumption of 37.4 watts, luminous flux of 3300 lumens, colour temperature of 2700 Kelvin and a high colour reproduction index of over 90. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.

## TECHNICAL DATA

Item no.	1003700
Number of different light outlets	1
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	1050 mA
Safety class	III
Wattage	37.4 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	3300 lm
Colour temperature	2700 Kelvin
Beam angle	40 °
Color	black
CRI	90
UGR ≤	22
LXXBXX data	L80B50
Service life	50000 h
Light distribution	rotational symmetric

## Light Source

791857	
--------	---

## Accessories

1006152	Numinos® XL Reducing ring , round 240/180mm white
1006151	Numinos® XL Reducing ring , round 240/180mm black
1004800	NUMINOS® XL , diffuser Frosted
1004071	LED driver 4.2-50W 1050mA DALI
1006454	RF module Casambi for LED bridge driver , single colour
1006154	Numinos® XL Reducing ring , square 240/180mm white
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1004798	NUMINOS® XL , diffuser Ellipse
1006153	Numinos® XL Reducing ring , square 240/180mm black
1004059	LED driverm 40W multi mA
1006461	LED bridge driver , 42W, 1050mA for NUMINOS®, including radio interface for RF module, DALI
1004066	LED driver , 28-40W 1000mA PHASE
1004801	NUMINOS® XL , diffuser Wabe
1004799	NUMINOS® XL , diffuser Prisma

Light outlet	direct
Risk Group	1
Height	11.8 cm
Diameter	19 cm
Net weight	0.7 kg
Gross weight	0.89 kg
Shape of cut-out	round
Installation depth	13 cm
Installation diameter	17.5 cm
BIG WHITE Page	87