



## NUMINOS® DL S

Indoor LED recessed ceiling light white/chrome 4000K  
20° gimballed, rotating and pivoting, including leaf  
springs

The NUMINOS light system from SLV perfectly combines function, design and technology. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. This also includes NUMINOS® DL S, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light has a power consumption of 8.6 watts, a luminous flux of 750 lumens, a colour temperature of 4000 Kelvin and a good colour reproduction index of over 90. Installation is then done in no time at all. When do you choose NUMINOS® from SLV?

## TECHNICAL DATA

|                                   |                      |
|-----------------------------------|----------------------|
| Item no.                          | 1003831              |
| Number of different light outlets | 1                    |
| IP Code                           | IP 20 / IP 44        |
| Impact resistance class           | IK 02                |
| Impact resistance                 | 0.2 Joule            |
| Assembly                          | Recessed             |
| Assembly details                  | Ceiling              |
| Secondary power / voltage         | 250 mA               |
| Safety class                      | III                  |
| Wattage                           | 8.6 W                |
| Minimum ambient temperature       | -20 °C               |
| Maximum ambient temperature       | 40 °C                |
| Lumen                             | 750 lm               |
| Colour temperature                | 4000 Kelvin          |
| Beam angle                        | 20 °                 |
| Color                             | white                |
| CRI                               | 90                   |
| UGR ≤                             | 19                   |
| LXXBXX data                       | L80B50               |
| Service life                      | 50000 h              |
| Light distribution                | rotational symmetric |
| Light outlet                      | direct               |

## Light Source

|        |   |
|--------|---|
| 791831 |  |
|--------|---|

### Accessories

|         |  |
|---------|--|
| 1006136 | Numinos® XS Reducing ring , round 160/70mm white   |
| 1006458 | LED bridge driver , 12W, 250mA for NUMINOS®, including radio interface for RF module, DALI |
| 1006135 | Numinos® XS Reducing ring , round 160/70mm black   |
| 1004789 | NUMINOS® S , diffuser Wabe   |
| 1004067 | LED driver , 15W 250mA DALI  |
| 1004788 | NUMINOS® S , diffuser Frosted  |
| 1004787 | NUMINOS® S , diffuser Prisma   |
| 1004786 | NUMINOS® S , diffuser Ellipse  |
| 1006454 | RF module Casambi for LED bridge driver , single colour                                    |
| 1004058 | LED driver , 6.5-10W 250mA   |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour                                |
| 1006137 | Numinos® XS Reducing ring , square 160/70mm black  |
| 1006138 | Numinos® XS Reducing ring , square 160/70mm white  |
| 1004055 | LED driver , 6.5-10W 250mA PHASE   |

|                       |         |
|-----------------------|---------|
| Risk Group            | 1       |
| Height                | 5.2 cm  |
| Diameter              | 8 cm    |
| Net weight            | 0.16 kg |
| Gross weight          | 0.2 kg  |
| Shape of cut-out      | round   |
| Installation depth    | 5.5 cm  |
| Installation diameter | 6.8 cm  |
| BIG WHITE Page        | 87      |