



## NUMINOS® DL M

Indoor LED recessed ceiling light black/black 3000K 40°

The NUMINOS light system from SLV skilfully combines function, design and technology. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Also with the NUMINOS® DL M recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light can convince with a power consumption of 17.55 watts, luminous flux of 1500 lumens, colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. This means that simple installation is a mere formality. When will you choose SLV's modular variety?

## TECHNICAL DATA

Item no.	1003868
Number of different light outlets	1
IP Code	IP 20 / IP 44
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	500 mA
Safety class	III
Wattage	17.55 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	1500 lm
Colour temperature	3000 Kelvin
Beam angle	40 °
Color	black
CRI	90
UGR ≤	22
LXXBXX data	L80B50
Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct

## Light Source

791822	
--------	---

## Accessories

1004792	NUMINOS® M , diffuser Frosted
1004069	LED driver , 29W 500mA
1004064	LED driver , 21-29.5W 500/600/700mA
1006459	LED bridge driver , 42W, 500mA for NUMINOS®, including radio interface for RF module, DALI
1004054	LED driver , 20W 500mA PHASE
1006139	Numinos® S Reducing ring , round 160/100mm black
1006454	RF module Casambi for LED bridge driver , single colour
1004793	NUMINOS® M , diffuser Wabe
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1006140	Numinos® S Reducing ring , round 160/100mm white
1006142	Numinos® S Reducing ring , square 160/100mm white
1004790	NUMINOS® M , diffuser Ellipse
1004791	NUMINOS® M , diffuser Prisma
1006141	Numinos® S Reducing ring , square 160/100mm black

Risk Group	1
Height	6.8 cm
Diameter	10.5 cm
Net weight	0.24 kg
Gross weight	0.28 kg
Shape of cut-out	round
Installation depth	7.5 cm
Installation diameter	9 cm
BIG WHITE Page	87