



## NUMINOS® DL L

Indoor LED recessed ceiling light white/black 2700K 40°

The NUMINOS light system from SLV perfectly combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Also with the NUMINOS® DL L recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light can convince with a power consumption of 25.41 watts, luminous flux of 2150 lumens, colour temperature of 2700 Kelvin and a high colour reproduction index of over 90. This means that simple installation is a mere formality. When do you choose NUMINOS® from SLV?

## TECHNICAL DATA

|                                   |                      |
|-----------------------------------|----------------------|
| Item no.                          | 1003928              |
| Number of different light outlets | 1                    |
| IP Code                           | IP 20 / IP 44        |
| Impact resistance class           | IK 02                |
| Impact resistance                 | 0.2 Joule            |
| Assembly                          | Recessed             |
| Assembly details                  | Ceiling              |
| Secondary power / voltage         | 700 mA               |
| Safety class                      | III                  |
| Wattage                           | 25.41 W              |
| Minimum ambient temperature       | -20 °C               |
| Maximum ambient temperature       | 40 °C                |
| Lumen                             | 2150 lm              |
| Colour temperature                | 2700 Kelvin          |
| Beam angle                        | 40 °                 |
| Color                             | white                |
| CRI                               | 90                   |
| UGR ≤                             | 22                   |
| LXXBXX data                       | L80B50               |
| Service life                      | 50000 h              |
| Light distribution                | rotational symmetric |
| Light outlet                      | direct               |

## Light Source

|        |   |
|--------|---|
| 791800 |  |
|--------|---|

## Accessories

|         |   |
|---------|---|
| 1004062 | LED driver , 21-29.5W<br>500/600/700mA for Numi-<br>nos Downlight Serie                             |
| 1004795 | NUMINOS® L , diffuser<br>Prisma   |
| 1004796 | NUMINOS® L , diffuser<br>Frosted  |
| 1006143 | Numinos® M Reducing<br>ring , round 240/120mm<br>black  |
| 1006460 | LED bridge driver , 42W,<br>700mA for NUMINOS®,<br>including radio interface<br>for RF module, DALI |
| 1004794 | NUMINOS® L , diffuser<br>Ellipse  |
| 1006146 | Numinos® M Reducing<br>ring , square 240/120mm<br>white   |
| 1006454 | RF module Casambi for<br>LED bridge driver , single<br>colour                                       |
| 1006144 | Numinos® M Reducing<br>ring , round 240/120mm<br>white  |
| 1006199 | RF module Zigbee for<br>DALI LED bridge driver ,<br>single colour                                   |
| 1004070 | LED driver , 40W 700mA<br>DALI  |
| 1006145 | Numinos® M Reducing<br>ring , square 240/120mm<br>black   |
| 1004797 | NUMINOS® L , diffuser<br>Wabe   |
| 1004065 | LED driver , 30W 700mA  |

|                       |          |
|-----------------------|----------|
| Risk Group            | 1        |
| Height                | 8.5 cm   |
| Diameter              | 13 cm    |
| Net weight            | 0.465 kg |
| Gross weight          | 0.525 kg |
| Shape of cut-out      | round    |
| Installation depth    | 9 cm     |
| Installation diameter | 11.7 cm  |
| BIG WHITE Page        | 87       |