



## NUMINOS® DL XL

**Indoor LED recessed ceiling light white/white 4000K 20°**

The NUMINOS light system from SLV combines technology, design and functionality like no other. With various downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® DL XL recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light can convince with a power consumption of 37.4 watts, luminous flux of 3800 lumens, colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. This means that easy installation is a mere formality. When will you choose SLV's modular variety?

## TECHNICAL DATA

<b>Item no.</b>	1004046
<b>Number of different light outlets</b>	1
<b>IP Code</b>	IP 20 / IP 44
<b>Impact resistance class</b>	IK 02
<b>Impact resistance</b>	0.2 Joule
<b>Assembly</b>	Recessed
<b>Assembly details</b>	Ceiling
<b>Secondary power / voltage</b>	1050 mA
<b>Safety class</b>	III
<b>Wattage</b>	37.4 W
<b>Minimum ambient temperature</b>	-20 °C
<b>Maximum ambient temperature</b>	40 °C
<b>Lumen</b>	3800 lm
<b>Colour temperature</b>	4000 Kelvin
<b>Beam angle</b>	20 °
<b>Color</b>	white
<b>CRI</b>	90
<b>UGR ≤</b>	19
<b>LXXBXX data</b>	L80B50
<b>Service life</b>	50000 h
<b>Light distribution</b>	rotational symmetric
<b>Light outlet</b>	direct

## Light Source

791850	
--------	---

## Accessories

1006148	Numinos® L Reducing ring , round 240/150mm white
1006149	Numinos® L Reducing ring , square 240/150mm black
1004800	NUMINOS® XL , diffuser Frosted
1004071	LED driver 4.2-50W 1050mA DALI
1006150	Numinos® L Reducing ring , square 240/150mm white
1006454	RF module Casambi for LED bridge driver , single colour
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1006147	Numinos® L Reducing ring , round 240/150mm black
1004798	NUMINOS® XL , diffuser Ellipse
1004059	LED driverm 40W multi mA
1006461	LED bridge driver , 42W, 1050mA for NUMINOS®, including radio interface for RF module, DALI
1004066	LED driver , 28-40W 1000mA PHASE
1004801	NUMINOS® XL , diffuser Wabe
1004799	NUMINOS® XL , diffuser Prisma

Risk Group	1
Height	10.8 cm
Diameter	16 cm
Net weight	0.715 kg
Gross weight	0.87 kg
Shape of cut-out	round
Installation depth	11.5 cm
Installation diameter	14.5 cm
BIG WHITE Page	87