



## 3~ NUMINOS® PHASE S

**3 phase system light white/black 4000K 36°**

The NUMINOS light system from SLV skilfully combines function, design and technology. With a variety of down-lights and spotlights, you provide a thousand lighting design options. Also with the 3~ NUMINOS® PHASE S 3-phase system light LED, which convinces with best workmanship and light quality. The spotlight is ideal for targeted accent lighting or for illuminating larger areas. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 1100 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

## TECHNICAL DATA

|                                 |                           |
|---------------------------------|---------------------------|
| Item no.                        | 1004095                   |
| Rotating or tilting             | rotary Bar and tiltable   |
| Assembly details                | Track Ceiling, Track Wall |
| Dimmable                        | Yes                       |
| Dimming technology              | trailing edge             |
| Primary nominal voltage         | 220-240V ~50/60Hz         |
| Secondary power / voltage       | 250 mA                    |
| Safety class                    | I                         |
| Wattage                         | 10.42 W                   |
| Minimum ambient temperature     | -20 °C                    |
| Maximum ambient temperature     | 40 °C                     |
| Number of luminaires at LS B16A | 88                        |
| Number of luminaires at LS C16A | 88                        |
| Level of inrush current         | 8.5 A                     |
| Duration of inrush current      | 60 µs                     |
| Lumen                           | 1100 lm                   |
| Colour temperature              | 4000 Kelvin               |
| Beam angle                      | 36 °                      |
| Color                           | white                     |
| CRI                             | 90                        |
| UGR ≤                           | 16                        |
| LXXBXX data                     | L80B50                    |

## Light Source

|        |   |
|--------|---|
| 791831 |  |
|--------|---|

## Accessories

|         |                               |
|---------|-------------------------------|
| 1006167 | NUMINOS® S , white front ring |
|---------|-------------------------------|

|                    |                      |
|--------------------|----------------------|
| Service life       | 50000 h              |
| Light distribution | rotational symmetric |
| Light outlet       | direct               |
| Risk Group         | 1                    |
| Length             | 16.2 cm              |
| Height             | 14.5 cm              |
| Diameter           | 6.5 cm               |
| Net weight         | 0.5 kg               |
| Gross weight       | 0.8 kg               |
| BIG WHITE Page     | 112                  |