




## NUMINOS® SPOT PHA-SE S

## Indoor LED recessed ceiling light white/black 2700K $36^{\circ}$

The NUMINOS light system from SLV combines technology, design and functionality like no other. With a variety of downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® SPOT PHASE S indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. The spotlight is perfect for targeted accent lighting or even illumination of larger areas. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 985 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV - modular diversity awaits you.



## **TECHNICAL DATA**

| Item no.                        | 1004103                 |
|---------------------------------|-------------------------|
| Rotating or tilting             | rotary Bar and tiltable |
| Assembly                        | Surface                 |
| Assembly details                | Ceiling, Wall           |
| Dimmable                        | Yes                     |
| Dimming technology              | trailing edge           |
| Primary nominal voltage         | 220-240V ~50/60Hz       |
| Secondary power / voltage       | 250 mA                  |
| Safety class                    | I                       |
| Wattage                         | 10.42 W                 |
| Minimum ambient temperature     | -20 °C                  |
| Maximum ambient temperature     | 40 °C                   |
| Number of luminaires at LS B16A | 88                      |
| Number of luminaires at LS C16A | 88                      |
| Level of inrush current         | 8.5 A                   |
| Duration of inrush current      | 60 µs                   |
| Lumen                           | 985 lm                  |
| Colour temperature              | 2700 Kelvin             |
| Beam angle                      | 36 °                    |
| Color                           | white                   |
| CRI                             | 90                      |
| UGR≤                            | 16                      |
|                                 | •                       |





## Light Source

| 791819      | A F                           |
|-------------|-------------------------------|
| Accessories |                               |
| 1006167     | NUMINOS® S , white front ring |

| L80B50               |
|----------------------|
| 50000 h              |
| rotational symmetric |
| direct               |
| 1                    |
| 16.2 cm              |
| 14.5 cm              |
| 6.5 cm               |
| 0.58 kg              |
| 0.87 kg              |
| 100                  |
|                      |



