



## NUMINOS® CL PHASE S

Indoor LED surface ceiling light black/black 3000K 24°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. The diverse downlights and spotlights make a thousand lighting design options possible. Also with the NUMINOS® CL PHASE S indoor ceiling-mounted light LED, which convinces with the best workmanship and lighting quality. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 1020 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

## TECHNICAL DATA

|                                 |                   |
|---------------------------------|-------------------|
| Item no.                        | 1004130           |
| Assembly                        | Surface           |
| Assembly details                | Ceiling           |
| Dimmable                        | Yes               |
| Dimming technology              | trailing edge     |
| Primary nominal voltage         | 220-240V ~50/60Hz |
| Secondary power / voltage       | 250 mA            |
| Safety class                    | I                 |
| Wattage                         | 10.42 W           |
| Minimum ambient temperature     | -20 °C            |
| Maximum ambient temperature     | 40 °C             |
| Number of luminaires at LS B16A | 88                |
| Number of luminaires at LS C16A | 88                |
| Level of inrush current         | 8.5 A             |
| Duration of inrush current      | 60 µs             |
| Lumen                           | 1020 lm           |
| Colour temperature              | 3000 Kelvin       |
| Beam angle                      | 24 °              |
| Color                           | black             |
| CRI                             | 90                |
| UGR ≤                           | 13                |
| LXXBXX data                     | L80B50            |



## Light Source

|        |   |
|--------|---|
| 791815 |  |
|--------|---|

## Accessories

|         |                               |
|---------|-------------------------------|
| 1006167 | NUMINOS® S , white front ring |
|---------|-------------------------------|

|                    |                      |
|--------------------|----------------------|
| Service life       | 50000 h              |
| Light distribution | rotational symmetric |
| Light outlet       | direct               |
| Risk Group         | 1                    |
| Height             | 16.2 cm              |
| Diameter           | 6.5 cm               |
| Net weight         | 0.425 kg             |
| Gross weight       | 0.65 kg              |
| BIG WHITE Page     | 104                  |