



NUMINOS® CL PHASE S

Indoor LED surface ceiling light white/black 4000K 36°

The NUMINOS light system from SLV perfectly combines function, design and technology. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Also with the NUMINOS® CL PHASE S indoor ceiling-mounted light LED, which convinces with the best workmanship and lighting quality. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 1100 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

TECHNICAL DATA

| | |
|---------------------------------|-------------------|
| Item no. | 1004143 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 250 mA |
| Safety class | I |
| Wattage | 10.42 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Number of luminaires at LS B16A | 88 |
| Number of luminaires at LS C16A | 88 |
| Level of inrush current | 8.5 A |
| Duration of inrush current | 60 µs |
| Lumen | 1100 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 36 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 16 |
| LXXBXX data | L80B50 |

Light Source

| | |
|--------|---|
| 791831 |  |
|--------|---|

Accessories

| | |
|---------|-------------------------------|
| 1006167 | NUMINOS® S , white front ring |
|---------|-------------------------------|

| | |
|--------------------|----------------------|
| Service life | 50000 h |
| Light distribution | rotational symmetric |
| Light outlet | direct |
| Risk Group | 1 |
| Height | 16.2 cm |
| Diameter | 6.5 cm |
| Net weight | 0.425 kg |
| Gross weight | 0.65 kg |
| BIG WHITE Page | 104 |