


NUMINOS® PD PHASE S

Indoor LED pendant light white/black 2700K 60°

The NUMINOS light system from SLV skilfully combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. This also includes NUMINOS® PD PHASE S, which impresses as a pendant light with the best workmanship and lighting quality. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 980 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.	1004152
Assembly	Surface
Assembly details	Ceiling, Ceiling with Acc.
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	250 mA
Safety class	I
Wattage	10.42 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	88
Number of luminaires at LS C16A	88
Level of inrush current	8.5 A
Duration of inrush current	60 µs
Lumen	980 lm
Colour temperature	2700 Kelvin
Beam angle	60 °
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L80B50



Light Source

791819	
--------	---

Accessories

1006167	NUMINOS® S , white front ring
---------	-------------------------------

Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Height	16.2 cm
Diameter	6.5 cm
Pendant length	250 cm
Net weight	0.659 kg
Gross weight	0.987 kg
BIG WHITE Page	108