


NUMINOS® PD PHASE S

Indoor LED pendant light white/black 4000K 60°

The NUMINOS light system from SLV skilfully combines function, design and technology. With a variety of down-lights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® PD PHASE S pendant light, which impresses with its high-quality workmanship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The pendant light has a power consumption of 10.42 watts, a luminous flux of 1100 lumens, a colour temperature of 4000 Kelvin and a good colour reproduction index of over 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

Item no.	1004168
Assembly	Surface
Assembly details	Ceiling, Ceiling with Acc.
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	250 mA
Safety class	I
Wattage	10.42 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	88
Number of luminaires at LS C16A	88
Level of inrush current	8.5 A
Duration of inrush current	60 µs
Lumen	1100 lm
Colour temperature	4000 Kelvin
Beam angle	60 °
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L80B50



Light Source

791831	
--------	---

Accessories

1006167	NUMINOS® S , white front ring
---------	-------------------------------

Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Height	16.2 cm
Diameter	6.5 cm
Pendant length	250 cm
Net weight	0.682 kg
Gross weight	0.912 kg
BIG WHITE Page	108