




NUMINOS® SPOT PHASE M

Indoor LED recessed ceiling light white/black 2700K 36°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® SPOT PHASE M indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. The spotlight is perfect for targeted accent lighting or even illumination of larger areas. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 1935 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

Item no.	1004199
Rotating or tilting	rotary Bar and tiltable
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20.1 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Number of luminaires at LS B16A	50
Number of luminaires at LS C16A	85
Level of inrush current	13 A
Duration of inrush current	30 µs
Lumen	1935 lm
Colour temperature	2700 Kelvin
Beam angle	36 °
Color	white
CRI	90
UGR ≤	16



Light Source

791800	
--------	--

Accessories

1006168	NUMINOS® M , white front ring
---------	-------------------------------

LXXBXX data	L80B50
Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Length	18.5 cm
Height	16.5 cm
Diameter	8.5 cm
Net weight	0.83 kg
Gross weight	1.125 kg
BIG WHITE Page	100