




NUMINOS® SPOT PHA-SE M

Indoor LED recessed ceiling light white/black 4000K 24°

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Also with the NUMI-NOS® SPOT PHASE M indoor ceiling-mounted light LED, which convinces with the best workmanship and lighting quality. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 2125 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

| Item no. | 1004214 |
|---------------------------------|-------------------------|
| Rotating or tilting | rotary Bar and tiltable |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 500 mA |
| Safety class | I |
| Wattage | 20.1 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 30 °C |
| Number of luminaires at LS B16A | 50 |
| Number of luminaires at LS C16A | 85 |
| Level of inrush current | 13 A |
| Duration of inrush current | 30 µs |
| Lumen | 2125 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 24° |
| Color | white |
| CRI | 90 |
| UGR≤ | 19 |
| | · |





Light Source

| 791825 | â E |
|-------------|-------------------------------|
| Accessories | |
| 1006168 | NUMINOS® M , white front ring |

| LXXBXX data | L80B50 |
|--------------------|----------------------|
| Service life | 50000 h |
| Light distribution | rotational symmetric |
| Light outlet | direct |
| Risk Group | 1 |
| Length | 18.5 cm |
| Height | 16.5 cm |
| Diameter | 8.5 cm |
| Net weight | 0.83 kg |
| Gross weight | 1.125 kg |
| BIG WHITE Page | 100 |
| | |



