



NUMINOS® CL PHASE M

Indoor LED surface ceiling light black/black 2700K 36°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you provide a thousand lighting design possibilities. Like with the NUMINOS® CL PHASE M indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 1935 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

TECHNICAL DATA

Item no.	1004219
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20.1 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Number of luminaires at LS B16A	50
Number of luminaires at LS C16A	85
Level of inrush current	13 A
Duration of inrush current	30 µs
Lumen	1935 lm
Colour temperature	2700 Kelvin
Beam angle	36 °
Color	black
CRI	90
UGR ≤	16
LXXBXX data	L80B50



Light Source

791800	
--------	---

Accessories

1006168	NUMINOS® M , white front ring
---------	-------------------------------

Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Height	18.5 cm
Diameter	8.5 cm
Net weight	0.68 kg
Gross weight	0.93 kg
BIG WHITE Page	104