



NUMINOS® CL PHASE M

Indoor LED surface ceiling light white/black 3000K 24°

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. The different downlights and spotlights make a thousand lighting design options possible. Also with the NUMINOS® CL PHASE M indoor ceiling-mounted light LED, which convinces with the best workmanship and lighting quality. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 1955 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When will you choose SLV's modular variety?

TECHNICAL DATA

Item no.	1004230
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20.1 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Number of luminaires at LS B16A	50
Number of luminaires at LS C16A	85
Level of inrush current	13 A
Duration of inrush current	30 µs
Lumen	1955 lm
Colour temperature	3000 Kelvin
Beam angle	24 °
Color	white
CRI	90
UGR ≤	16
LXXBXX data	L80B50



Light Source

791822	
--------	---

Accessories

1006168	NUMINOS® M , white front ring
---------	-------------------------------

Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Height	18.5 cm
Diameter	8.5 cm
Net weight	0.68 kg
Gross weight	0.93 kg
BIG WHITE Page	104