



3~ NUMINOS® PHASE L

3 phase system light black/black 2700K 60°

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Also with the 3~ NUMINOS® PHASE L 3-phase system light LED, which convinces with best workmanship and light quality. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. The recessed ceiling light convinces with a power consumption of 28 watts, luminous flux of 2475 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.

TECHNICAL DATA

Item no.	1004268
Rotating or tilting	rotary Bar and tiltable
Assembly details	Track Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	28 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Number of luminaires at LS B16A	34
Number of luminaires at LS C16A	58
Level of inrush current	6 A
Duration of inrush current	40 µs
Lumen	2475 lm
Colour temperature	2700 Kelvin
Beam angle	60 °
Color	black
CRI	90
UGR ≤	22
LXXBXX data	L80B50



Light Source

791800	
--------	---

Accessories

1006169	NUMINOS® L , white front ring
---------	-------------------------------

Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Length	21.3 cm
Height	18 cm
Diameter	10 cm
Net weight	1.07 kg
Gross weight	1.4 kg
BIG WHITE Page	113