




## NUMINOS® SPOT PHASE L

Indoor LED recessed ceiling light black/black 2700K 24°

The NUMINOS light system from SLV skilfully combines function, design and technology. With various downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® SPOT PHASE L indoor ceiling-mounted light LED, which convinces with the best workmanship and lighting quality. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 28 watts, luminous flux of 2440 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMINOS® from SLV?



### TECHNICAL DATA

|                                 |                         |
|---------------------------------|-------------------------|
| Item no.                        | 1004290                 |
| Rotating or tilting             | rotary Bar and tiltable |
| Assembly                        | Surface                 |
| Assembly details                | Ceiling                 |
| Dimmable                        | Yes                     |
| Dimming technology              | trailing edge           |
| Primary nominal voltage         | 220-240V ~50/60Hz       |
| Secondary power / voltage       | 700 mA                  |
| Safety class                    | I                       |
| Wattage                         | 28 W                    |
| Minimum ambient temperature     | -20 °C                  |
| Maximum ambient temperature     | 30 °C                   |
| Number of luminaires at LS B16A | 34                      |
| Number of luminaires at LS C16A | 58                      |
| Level of inrush current         | 6 A                     |
| Duration of inrush current      | 40 µs                   |
| Lumen                           | 2440 lm                 |
| Colour temperature              | 2700 Kelvin             |
| Beam angle                      | 24 °                    |
| Color                           | black                   |
| CRI                             | 90                      |
| UGR ≤                           | 19                      |



## Light Source

|        |   |
|--------|---|
| 791800 |  |
|--------|---|

## Accessories

|         |                               |
|---------|-------------------------------|
| 1006169 | NUMINOS® L , white front ring |
|---------|-------------------------------|

|                    |                      |
|--------------------|----------------------|
| LXXBXX data        | L80B50               |
| Service life       | 50000 h              |
| Light distribution | rotational symmetric |
| Light outlet       | direct               |
| Risk Group         | 1                    |
| Length             | 21.3 cm              |
| Height             | 18 cm                |
| Diameter           | 10 cm                |
| Net weight         | 1.08 kg              |
| Gross weight       | 1.425 kg             |
| BIG WHITE Page     | 101                  |