




NUMINOS® SPOT PHASE L

Indoor LED recessed ceiling light white/black 3000K 36°

The NUMINOS light system from SLV perfectly combines function, design and technology. With a variety of downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® SPOT PHASE L indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 28 watts, luminous flux of 2340 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

Item no.	1004303
Rotating or tilting	rotary Bar and tiltable
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	28 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Number of luminaires at LS B16A	34
Number of luminaires at LS C16A	58
Level of inrush current	6 A
Duration of inrush current	40 µs
Lumen	2340 lm
Colour temperature	3000 Kelvin
Beam angle	36 °
Color	white
CRI	90
UGR ≤	13



Light Source

791822	
--------	---

Accessories

1006169	NUMINOS® L , white front ring
---------	-------------------------------

LXXBXX data	L80B50
Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Length	21.3 cm
Height	18 cm
Diameter	10 cm
Net weight	1.08 kg
Gross weight	1.425 kg
BIG WHITE Page	101

