




NUMINOS® SPOT PHA-SE L

Indoor LED recessed ceiling light black/black 4000K 36°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. The diverse downlights and spotlights make a thousand lighting design options possible. Like with the NUMINOS® SPOT PHASE L indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 28 watts, luminous flux of 2620 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV - modular diversity awaits you.



TECHNICAL DATA

| Item no. | 1004307 |
|---------------------------------|-------------------------|
| Rotating or tilting | rotary Bar and tiltable |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 700 mA |
| Safety class | I |
| Wattage | 28 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 30 °C |
| Number of luminaires at LS B16A | 34 |
| Number of luminaires at LS C16A | 58 |
| Level of inrush current | 6 A |
| Duration of inrush current | 40 µs |
| Lumen | 2620 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 36 ° |
| Color | black |
| CRI | 90 |
| UGR≤ | 19 |
| | |





Light Source

| 791825 | â E |
|-------------|-------------------------------|
| Accessories | |
| 1006169 | NUMINOS® L , white front ring |

| LXXBXX data | L80B50 |
|--------------------|----------------------|
| Service life | 50000 h |
| Light distribution | rotational symmetric |
| Light outlet | direct |
| Risk Group | 1 |
| Length | 21.3 cm |
| Height | 18 cm |
| Diameter | 10 cm |
| Net weight | 1.08 kg |
| Gross weight | 1.425 kg |
| BIG WHITE Page | 101 |
| | |



