




NUMINOS® SPOT PHA-SE L

Indoor LED recessed ceiling light white/black 4000K 36°

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Also with the NUMINO-S® SPOT PHASE L indoor ceiling-mounted light LED, which convinces with the best workmanship and lighting quality. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. The recessed ceiling light convinces with a power consumption of 28 watts, luminous flux of 2620 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

Item no.	1004311
Rotating or tilting	rotary Bar and tiltable
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	28 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Number of luminaires at LS B16A	34
Number of luminaires at LS C16A	58
Level of inrush current	6 A
Duration of inrush current	40 µs
Lumen	2620 lm
Colour temperature	4000 Kelvin
Beam angle	36 °
Color	white
CRI	90
UGR≤	19
	·





Light Source

791825	â E
Accessories	
1006169	NUMINOS® L , white front ring

LXXBXX data	L80B50
Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Length	21.3 cm
Height	18 cm
Diameter	10 cm
Net weight	1.08 kg
Gross weight	1.425 kg
BIG WHITE Page	101



