




NUMINOS® PD PHASE L

Indoor LED pendant light black/black 2700K 24°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With different downlights and spotlights, you provide a thousand lighting design possibilities. Also with the NUMINOS® PD PHASE L pendant light, which convinces with the best workmanship and lighting quality. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. The pendant light has a power consumption of 28 watts, a luminous flux of 2440 lumens, a colour temperature of 2700 Kelvin and a good colour reproduction index of over 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

| | |
|---------------------------------|-------------------|
| Item no. | 1004338 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 700 mA |
| Safety class | I |
| Wattage | 28 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 30 °C |
| Number of luminaires at LS B16A | 34 |
| Number of luminaires at LS C16A | 58 |
| Level of inrush current | 6 A |
| Duration of inrush current | 40 µs |
| Lumen | 2440 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 24 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 19 |
| LXXBXX data | L80B50 |



Light Source

| | |
|--------|---|
| 791800 |  |
|--------|---|

Accessories

| | |
|---------|-------------------------------|
| 1006169 | NUMINOS® L , white front ring |
|---------|-------------------------------|

| | |
|--------------------|----------------------|
| Service life | 50000 h |
| Light distribution | rotational symmetric |
| Light outlet | direct |
| Risk Group | 1 |
| Height | 21.3 cm |
| Diameter | 10 cm |
| Pendant length | 250 cm |
| Net weight | 1.25 kg |
| Gross weight | 1.559 kg |
| BIG WHITE Page | 109 |

