




## NUMINOS® PD PHASE L

Indoor LED pendant light white/black 4000K 24°

The NUMINOS light system from SLV perfectly combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Also with the NUMINOS® PD PHASE L pendant light, which convinces with the best workmanship and lighting quality. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The pendant light has a power consumption of 28 watts, a luminous flux of 2675 lumens, a colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



## TECHNICAL DATA

Item no.	1004358
Assembly	Surface
Assembly details	Ceiling,Ceiling with Acc.
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	28 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Number of luminaires at LS B16A	34
Number of luminaires at LS C16A	58
Level of inrush current	6 A
Duration of inrush current	40 µs
Lumen	2675 lm
Colour temperature	4000 Kelvin
Beam angle	24 °
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L80B50



## Light Source

791825	
--------	---

## Accessories

1006169	NUMINOS® L , white front ring
---------	-------------------------------

Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Height	21.3 cm
Diameter	10 cm
Pendant length	250 cm
Net weight	1.3 kg
Gross weight	1.5 kg
BIG WHITE Page	109