



3~ NUMINOS® DALI S

3 phase system light black/black 3000K 36°

The NUMINOS light system from SLV skilfully combines function, design and technology. The diverse downlights and spotlights make a thousand lighting design options possible. Like with the 3~ NUMINOS® DALI S 3-phase system light LED, which impresses with its high-quality workmanship and light. The spotlight is ideal for targeted accent lighting or for illuminating larger areas. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 1020 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.

TECHNICAL DATA

Item no.	1004371
Rotating or tilting	rotary Bar and tiltable
Assembly details	Track Ceiling, Track Wall
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	250 mA
Safety class	I
Wattage	10.42 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	72
Number of luminaires at LS C16A	122
Level of inrush current	52 A
Duration of inrush current	1 µs
Lumen	1020 lm
Colour temperature	3000 Kelvin
Beam angle	36 °
Color	black
CRI	90
UGR ≤	13
LXXBXX data	L80B50



Light Source

791815	
--------	---

Accessories

1006167	NUMINOS® S , white front ring
---------	-------------------------------

Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Length	16.2 cm
Height	14.5 cm
Diameter	6.5 cm
Net weight	0.56 kg
Gross weight	0.85 kg
BIG WHITE Page	112