



NUMINOS® CL DALI S

Indoor LED surface ceiling light black/black 2700K 36°

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Also with the NUMINOS® CL DALI S indoor ceiling-mounted light LED, which convinces with the best workmanship and lighting quality. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 985 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When will you choose SLV's modular variety?

TECHNICAL DATA

| | |
|---------------------------------|-------------------|
| Item no. | 1004411 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | DALI |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 250 mA |
| Safety class | I |
| Wattage | 10.42 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Number of luminaires at LS B16A | 72 |
| Number of luminaires at LS C16A | 122 |
| Level of inrush current | 52 A |
| Duration of inrush current | 1 µs |
| Lumen | 985 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 36 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 16 |
| LXXBXX data | L80B50 |



Light Source

| | |
|--------|---|
| 791819 |  |
|--------|---|

Accessories

| | |
|---------|-------------------------------|
| 1006167 | NUMINOS® S , white front ring |
|---------|-------------------------------|

| | |
|--------------------|----------------------|
| Service life | 50000 h |
| Light distribution | rotational symmetric |
| Light outlet | direct |
| Risk Group | 1 |
| Height | 16.2 cm |
| Diameter | 6.5 cm |
| Net weight | 0.56 kg |
| Gross weight | 0.725 kg |
| BIG WHITE Page | 104 |

