



NUMINOS® CL DALI S

Indoor LED surface ceiling light white/black 2700K 24°

NUMINOS is the perfectly coordinated light system from SLV that combines function, design and technology. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® CL DALI S indoor ceiling-mounted light LED, which convinces with the best workmanship and lighting quality. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 985 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

TECHNICAL DATA

Item no.	1004414
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	250 mA
Safety class	I
Wattage	10.42 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	72
Number of luminaires at LS C16A	122
Level of inrush current	52 A
Duration of inrush current	1 µs
Lumen	985 lm
Colour temperature	2700 Kelvin
Beam angle	24 °
Color	white
CRI	90
UGR ≤	16
LXXBXX data	L80B50



Light Source

791819	
--------	---

Accessories

1006167	NUMINOS® S , white front ring
---------	-------------------------------

Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Height	16.2 cm
Diameter	6.5 cm
Net weight	0.56 kg
Gross weight	0.725 kg
BIG WHITE Page	104

